

# TASKI® swingo 1255B BMS Battery Powered Medium Scrubber Drier

Medium battery powered walk behind

## swingo 1255B BMS Kit 4

CODE	
D7516831ANZ-KIT4	1 x TASKI swingo 1255B BMS
	4 x Battery traction 12V 76Ah
	2 x Standard scrubbing brush 28 cm

## swingo 1255B BMS Kit 5

CODE	
D7516831ANZ-KIT5	1 x TASKI swingo 1255B BMS
	4 x Battery traction 12V 76Ah
	2 x Pad drive harpoon grip 28 cm

## swingo 1255B BMS Kit 6

CODE	
D7516831ANZ-KIT6	1 x TASKI swingo 1255B BMS
	4 x Battery traction 12V 76Ah
	2 x Standard scrubbing brush 28 cm
	2 x Pad drive harpoon grip 28 cm

## swingo 1255B BMS Optional Accessories

CODE	
D7520152	Battery traction 12V 76Ah (4 req'd)
D7510634	Pad drive harpoon grip 28 cm
D7519395	Scrubbing brush standard 28 cm
D7510632	Scrubbing brush washed concr. 28cm
D7510633	Scrubbing brush abrasive 28 cm
D7523390	TASKI IntelliTrail hardware
D4131643	Retro fit kit IntelliTrail 755/1255
D7517125	TASKI IntelliDose 755/1255
D6093818	TASKI IntelliPad - 11 inch (28cm)

### Ideal size for best performance

The patented IntelliFlow-system always ensures the right amount of cleaning solution on the floor and leads to significant water savings. This, in combination with the 60L tank volume, increases productivity and cuts the number of time consuming tank filling stops during the cleaning operation. The dual-axle system ensures easy handling and allows comfortable use of the machine.

### Excellent cleaning and drying results

The patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width. The 2 brushes with offset to side allow perfect cleaning along walls and under racks. This results in excellent soil removal and floor appearance. The patented V-shaped squeegee allows perfect water pick-up on all floor types, even on structured and grouted/tiled floors. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven 3-wheel concept, adjustments of the squeegee are not necessary any more.

### Durability and robustness

The use of high tech material and long life components enhance the machine's uptime while reducing service and repair costs to a minimum.

### Maintenance

Colour coded maintenance points increase efficiency and reduce the need for training. Fewer parts to maintain and easy accessibility make the machine extremely service friendly.



Technical data	
Theoretical performance	2475m <sup>2</sup> /h
Working width	55cm
Squeegee width	80cm
Solution tank (nominal)	60L
Recovery tank (nominal)	60L
Nominal consumption	1000W
Rated voltage	24V
Battery capacity	100-140 Ah/C5
Battery autonomy (nominal)	Up to 3 hours
Machine weight ready for use	260kg
Dimensions (L x W x H)	1420 x 580 x 1170mm
Turning circle	1.33m
Brush system	2 x 28cm
Brush pressure (with/without wheel drive)	48kg
Working speed	4.5km/h
Cable length of integrated battery charger	3m
Sound level	58 dB(A)
Electrical protection class	Class II/III
Approvals	CE/CB Test cert./ÖVE/cETL